

# CST-M10/78BH

# 590-600W PERC

156 HALF-CELL MONOFACIAL ALL-BLACK MODULE

## Characteristic



**Super Safety and Reliability**  
No hidden welding crack, low operating temperature, high pressure resistance.



**Low Hot Spot Risk**  
Parallel circuit design reduces shading loss.



**Beautiful Appearance**  
Uniform layout, better aesthetic.




**Low System Cost**  
High module efficiency, reducing system cost.

**21.7%**


Max Module  
Efficiency

## Consort Linear Warranty




- 12 year Product Warranty
- 25 Year Linear Power Warranty
- 0.55% Annual Degradation Over 25 Years


## ENGINEERING DRAWING (mm)




## FRAME CROSS SECTION (mm)



## I-V/P-V CURVE AT DIFFERENT IRRADIATION (600W)



## I-V CURVE AT DIFFERENT TEMPERATURE (600W)



## Electrical Characteristics (STC/NMOT)

PV module model	CST-M10/78BH 585		CST-M10/78BH 590		CST-M10/78BH 595		CST-M10/78BH 600	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power - Pmax(W)	585	442.7	590	446.5	595	450.4	600	454.1
Open Circuit Voltage - Voc(V)	53.89	50.88	54.15	51.12	54.41	51.37	54.65	51.60
Short Circuit Current - Isc(A)	13.63	10.91	13.66	10.94	13.69	10.96	13.72	10.99
Voltage at Pmax-Vmp(V)	45.56	42.26	45.88	42.55	46.20	42.85	46.51	43.14
Current at Pmax-Imp(A)	12.84	10.48	12.86	10.49	12.88	10.51	12.90	10.53
Module Efficiency-ηm(%)	21.1		21.3		21.5		21.7	
Power Output Tolerance(W)	0~+5							

STC: Irradiance 1000 W/m<sup>2</sup>, Module Temperature 25°C, Air Mass AM1.5

NMOT: Irradiance 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s

## Mechanical Data

Number of Cells	182mm monocrystalline 156 pieces(78x2)
External Dimensions	2443x1134x30mm
Weight	31kg
Front glass	High transparency solar glass 3.2mm
Frame	Black, Anodized aluminum alloy
Junction Box	IP68 rated
Output Cables	4.0mm <sup>2</sup> , 280 mm in length,length can be customized/UV resistant
Wind/Snow Load	2400Pa/5400Pa
Connector	MC4 compatible

## Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	43±2°C
Isc Temperature Coefficient	+0.05%/°C
Voc Temperature Coefficient	-0.28%/°C
Pmax Temperature Coefficient	-0.36%/°C

## Maximum Ratings

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Max Series Fuse Rating	25A

Power measurement error + / - 3%

## Packaging Configuration

Module per pallet	36 pieces
Modules per 40' container	576 pieces

# PARAMETER